

# DRYER-D

## Specification Dehumidifier Model: DDH-138D

	Model	DDH-138D
	Series	Industrial
Voltage/Cycle	220V /50Hz	
Power Input (W)	1500W	
Running Current	6.8A	
Dehumidifying Capacity	138L/Day (30°C, 80%RH)	
Humidity Set	31% - 90% RH	
Humidity level can be set	+/- 1%RH	
Working mode humidity set	compressor stops when the desired humidity value is reached. But the fan is still working	
Timer On, Timer Off	Yes	
Display screen	Show Current humidity Show set humidity Show temperature	
Coverage area	130 - 180 sq.m (High 3 m)	
Refrigerant	R410A	
Air Flow	1300 m <sup>3</sup> /h , 765 cfm	
Drainage Method	Direct Drain	
Working temperature range	5°C- 38°C	
Maneuverability	4 Casters , Handle	
Control Type	Digital, Computer	
Sensor	Humidity sensor "RHI"	
Noise	≤60dBat a distance of 1 m.	
Compressor	Rotary	
Safety	3 min delay protection / Show failure code / Automatic Defrost	
Control Type	Digital Micro-Computer	
Color	White&Yellow	
Unit Dimension (mm.)	480*420*1080 (±5)	
N/W	65Kg (±2)	



## DRYER-D by MTS

บริษัท เอ็มทีเอสซีเอ็นซี ซิสเต็ม จำกัด 48/300 ซอยหทัยราษฎร์ 37 ถนนหทัยราษฎร์ แขวงสามวาตะวันตก เขตคลองสามวา กรุงเทพฯ 10510

Tel & Fax: 02-9067988, 081-4032224, 087-0520076, e-mail: [dservice@dryer-d.com](mailto:dservice@dryer-d.com), [www.dryer-d.com](http://www.dryer-d.com)